

Portée max.	GBA	
	14x19	19x19
1,00	39,0 kN/m	40,0 kN/m
	GBA 14x19/140	GBA 19x19/140
1,10		
1,20		
1,30		
1,40	31,0 kN/m	31,0 kN/m
	GBA 14x19/180	GBA 19x19/180
1,50		
1,60		
1,70		
1,80	26,0 kN/m	26,0 kN/m
	GBA 14x19/220	GBA 19x19/220
1,90		
2,00		
2,10		
2,20	22,0 kN/m	23,0 kN/m
	GBA 14x19/260	GBA 19x19/260
2,30		
2,40		
2,50		
2,60	18,0 kN/m	20,0 kN/m
	GBA 14x19/300	GBA 19x19/300
2,70		
2,80		
2,90		
3,00	13,0 kN/m	
	GBA 14x19/340	



Longueurs :

GBA 14x19 : 1,4m - 1,8m - 2,2m - 2,6m - 3m - 3,4m
 GBA 19x19 : 1,4m - 1,8m - 2,2m - 2,6m - 3m

Hauteur : 19cm

Largeurs : 14cm et 19cm

Poids des éléments :

GBA 14x19 : 66 kg/ml
 GBA 19x19 : 87 kg/ml

Appui : minimum 20cm

